

CERTIFIED FOR STORAGE AND TRANSPORT

**ADJUSTABLE PUMP
FRAME**

The DAYWALK Adjustable Pump Frame is a pre-engineered solution, offering world class adjustability and functionality for transporting multiple types of pumps safely, especially vertical sump pumps, meeting CoR requirements.



FEATURES / KEY BENEFITS



FORKLIFTABLE



ADJUSTABLE MOUNT RAILS



RESTRAINT LUGS



EXTERNAL 'TRUCK LASHING' LUGS



EFFICIENT SKELETAL DESIGN



QR GUIDANCE & SUPPORT

COMPATIBLE WITH SUMP PUMP VARIATIONS Not limited to these options, please contact Daywalk





SPECIFICATIONS

| | |
|------------------------------|--|
| Product Name | Hybrid Pump Transport Frame Kit (2 standard chocks + 2 stepped chocks to suit flat drive component guard base) |
| SKU | 13-PSDC/4500/1650/WHP |
| WLL | 3T |
| Coating/Material | Heavy Duty Powdercoated |
| Ext Dimensions | 4500mmL x 1650mmW |
| Inclusions | 4 x Lashing Lugs 8 x External Vehicle Lashing Lugs 9-way adjustable design Multiple centre of gravity positions Certification and ID Plaques |
| Rated | Logistics Engineered and Rated for Transport |
| Compatible Pumps | Fits pump lengths from 550 -2100mm (maximum base mounting 1900mm) |
| Compatibility | Forklift + DAYWALK Load Guide |
| Complies with | AS/NZS 1170.0 - 2002, AS/NZS 1170.1 - 2002, AS 4100 - 1998 + AS 4991 - 2004. |
| Colour | Safety Yellow |
| Australian Patent No. | 2021104657 |

DESIGN > LOGISTICS